

WHAT IS CLAIMED IS:

1. A method for parallel compression and
decompression of a bitstream, comprising:
separating a bitstream into a plurality of
5 components;
encoding the components using a compression
algorithm;
constructing packets from the encoded components,
where at least one packet is associated with each encoded
10 component and the at least one packet comprises header
information and encoded data;
combining the packets into a packetized encoded
bitstream;
separating packets from the packetized encoded
15 bitstream using the header information;
decoding packets in parallel using a decompression
algorithm to recover the encoded data;
constructing the plurality of components from the
recovered encoded data; and
20 combining the plurality of components to recover the
bitstream.

2. The method of Claim 1, wherein the bitstream is
a digitized graphics or video frame.

3. The method of Claim 2, wherein separating the
bitstream into a plurality of components comprises

separating the graphics or video frame into separate lines.

4. The method of Claim 2, wherein combining the plurality of components to recover the bitstream comprises recovering the digitized graphics or video frame for display.

5. The method of Claim 1, wherein encoding the components using a compression algorithm comprises encoding using a lossless compression format.

6. The method of Claim 1, wherein decoding packets in parallel using a decompression algorithm comprises encoding using a lossless compression format.

7. The method of Claim 1, wherein constructing packets from the encoded components comprises constructing variable-length packets.

8. The method of Claim 7, wherein the header information of the at least one packet comprises a size, a predictor and an alignment.

9. The method of Claim 8, wherein decoding packets in parallel comprises distributing packets to separate decode units in order.

10. The method of Claim 1, wherein constructing
packets from the encoded components comprises
constructing fixed-length packets.

5 11. The method of Claim 10, wherein the header
information of the at least one packet comprises a tag.

10 12. The method of Claim 11, wherein decoding
packets in parallel comprises distributing packets to
separate decode units based upon the tag.

13. A system for parallel compression and
decompression of a bitstream, comprising:

an encoder system comprising:

5 a plurality of encode units operable to receive
components separated from a bitstream and to encode the
components using a compression algorithm;

10 the encode units further operable to construct
packets from the encoded components, where at least one
packet is associated with each encoded component and the
at least one packet comprises header information and
encoded data; and

15 a multiplexer coupled to the encode units, the
multiplexer operable to combine the packets into a
packetized encoded bitstream; and

a decoder system comprising;

20 a feeder operable to separate packets from the
packetized encoded bitstream;

a plurality of decode queues, the feeder
further operable to distribute the packets to the decode
queues;

25 a plurality of decode units each associated
with one of the decode queues, the decode units operable
to decode packets using a decompression algorithm to
recover the encoded data and to reconstruct the
components; and

a demultiplexer coupled to the plurality of
decode units the demultiplexer operable to combine the
plurality of components to recover the bitstream.

D
14. The system of Claim 13, wherein the bitstream is a digitized graphics or video frame.

Sub 35
15. The system of Claim 14, wherein the plurality of components comprise separate lines of the digitized ~~graphics or video frame.~~

10 D
16. The system of Claim 14, wherein the demultiplexer combines the plurality of components to recover the digitized graphics or video frame for display.

15
17. The system of Claim 13, wherein the encode units use a lossless compression format for the compression algorithm.

20
18. The system of Claim 13, wherein the decode units use a lossless compression format for the decompression algorithm.

19. The system of Claim 13, wherein the encode units construct variable-length packets.

25
20. The system of Claim 19, wherein the header information of the at least one packet comprises a size, a predictor and an alignment.

21. The system of Claim 20, wherein the feeder distributes the packets to separate decode queues in order.

5 22. The system of Claim 20, wherein the feeder comprises:

an input queue operable to receive the packetized encoded bitstream;

a multiplexer coupled to the input queue;

10 a register coupled to the multiplexer;

a demultiplexer coupled to the register and to the decode queues; and

a left shift unit coupled to the register and to the multiplexer.

15 23. The system of Claim 13, wherein the encode units construct fixed-length packets.

20 24. The system of Claim 23, wherein the header information of the at least one packet comprises a tag.

25 25. The system of Claim 24, wherein the feeder distributes the packets to separate decode queues based upon the tag.

26. The system of Claim 24, wherein the feeder comprises an input queue operable to receive the packetized encoded bitstream.